

Aquadopp 300 m - Legacy

No longer available.
See new version.



This version of the Aquadopp is no longer available.

Please see the [Aquadopp Generation 2](#).

This version of the Aquadopp remains functional and supported. Please visit our [support center](#) if you require assistance.

Highlights

Applications

Technical specifications

Water velocity measurements

Maximum profiling range	N/A
Cell size	0.75 m
Minimum blanking	0.35 m
Maximum number of cells	1
Measurement cell position	0.35-5.0 m (user-selectable)
Default position (along beam)	0.35-1.85 m
Velocity range	±5 m/s
Accuracy	±1% of measured value ±0.5 cm/s
Velocity precision	Consult instrument software
Maximum sampling rate (output)	1 Hz, 4 Hz on request
Internal sampling rate	23 Hz

Echo intensity

Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	2 MHz
Number of beams	3
Beam width	3.4°

Sensors

Temperature:	Thermistor embedded in head
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	10 min
Compass:	Magnetometer
Accuracy/resolution	2°/0.1° for tilt < 20°
Tilt:	Liquid level
Accuracy/resolution	0.2°/0.1°
Maximum tilt	30°
Up or Down	Automatic detect
Pressure:	Piezoresistive
Range	300 m
Accuracy/precision	0.5% FS / 0.005% of full scale

Analogue inputs

No. of channels	2
Supply voltage to analog output devices	Three options selectable through firmware commands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
Voltage input	0-5 V
Resolution	16-bit A/D

Data recording

Capacity	9 MB, can add 4/16 GB
Data record	40 bytes
Diagnostics record	40 bytes
Wave record	40 bytes
Mode	Stop when full (default) or wrap mode

Real-time clock

Accuracy	±1 min/year
Backup in absence of power	4 weeks

Data communications

I/O	RS-232 or RS-422
Communication baud rate	300-115,200 Bd
Recorder download baud rate	600/1200 kBd for both RS-232 and RS-422
User control	Handled via "Aquadopp" software, ActiveX® function calls, or direct commands with binary or ASCII data output

Software

Functions	Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)
-----------	---

Power

DC input	9-15 V DC
Maximum peak current	3 A
Avg. power consumption	0.01 W
Sleep current	< 100 µA

Power

Transmit power	0.3-20 W, 3 adjustable levels
----------------	-------------------------------

Batteries

Battery capacity	1) 50 Wh (alkaline or Li-ion), 2) 165 Wh (lithium), 3) Single or dual
New battery voltage	13.5 V DC (alkaline)

Environmental

Operating temperature	-5 to +40 °C
Storage temperature	-20 to +60 °C
Shock and vibration	IEC 721-3-2
EMC approval	IEC 61000
Depth rating	300 m

Connectors

Bulkhead	MCBH-8-FS
Cable	PMCIL-8-MP on 10 m polyurethane cable

Materials

Standard model	POM housing
----------------	-------------

Dimensions

Maximum diameter	75 mm
Maximum length	~500 mm (single battery) or +110 mm (double battery) depending on head configuration

Weight

Weight in air	2.3 kg
Weight in water	Neutral