Aquadopp Profiler 600 kHz - Legacy

300 m



This version of the Aquadopp Profiler 600 kHz is no longer available.

Please see the Aquadopp Profiler 600kHz Generation 2.

This version of the Aquadopp remains functional and supported. Please visit our support center if you require assistance.

Highlights

Applications

Technical specifications

Water velocity measurements	
Maximum profiling range	30-40 m
Cell size	1-4 m
Minimum blanking	0.50 m
Maximum number of cells	96
Measurement cell position	N/A
Default position (along beam)	N/A
Velocity range	±10 m/s
Accuracy	±1% of measured value ±0.5 cm/s
Velocity precision	Consult instrument software
Maximum sampling rate (output)	1 Hz
Internal sampling rate	4 Hz

Echo intensity (along slanted beams)	
Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	600 kHz
Number of beams	3
Beam width	3.0°

HR option	
Maximum profiling range	N/A
Cell size	N/A

HR option

Minimum blanking	N/A
Maximum number of cells	N/A
Range/Velocity limitations	N/A
Accuracy	N/A
Max. sampling rate	N/A

Z-Cell option

Cell zero acoustic frequency	N/A
Maximum profiling range	N/A
Number of beams	N/A

Sensors

Temperature:	Thermistor embedded in head
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	10 min
Compass:	Magnetometer
Accuracy/resolution	2°/0.1° for tilt < 20°
Tilt:	Liquid level
Accuracy/resolution	0.2°/0.1°
Maximum tilt	30°
Up or Down	Automatic detect
Pressure:	Piezoresistive
Range	0-100 m (inquire for options)
Accuracy/precision	0.5% FS / 0.005% of full scale

Analog inputs

No. of channels	2
Supply voltage to analog output devices	Three options selectable through firmware commands:1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
Voltage input	0-5 V
Resolution	16-bit A/D

Data recording

Capacity	9 MB, can add 4/16 GB
Data record	9*Ncells + 32 bytes
Diagnostics record	N/A
Wave record	Nsamples * 24 + 60 bytes
Mode	Stop when full (default) or wrap mode

Real-time clock

Accuracy	±1 min/year
Backup in absence of power	4 weeks

Data communications

I/O	RS-232 or RS-422

Data communications

Communication baud rate	300-115200 Bd
Recorder download baud rate	600/1200 kBd for both RS-232 and RS-422
User control	Handled via "Aquadopp" software, ActiveX®function calls, or direct commands with binary or ASCII data output

Connectors

Bulkhead	MCBH-8-FS
Cable	PMCIL-8-MP on 10m polyurethane cable

Software

Functions	Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)

Power

DC input	9-15 V DC
Maximum peak current	3 A
Avg. power consumption	0.06 W
Sleep current	< 100 µA
Transmit power	0.3-20 W, 4 adjustable levels

Batteries

Battery capacity	1) 50 Wh (alkaline or Li-ion), 2) 165 Wh (lithium), 3) Single or dual
New battery voltage	13.5 V DC (alkaline)

Environmental

Operating temperature	-5 to +40 °C
Storage temperature	-20 to +60 °C
Shock and vibration	IEC 721-3-6
EMC approval	IEC 61000
Depth rating	300 m

Materials

Standard model	POM and polyurethane plastics with titanium fasteners

Dimensions

Maximum diameter	100 mm
Maximum length	~550 mm (single battery), +110 mm (double battery) depending on head configuration

Weight

Weight in air	2.9 kg
Weight in water	0.4 kg

Options

1) Alkaline, lithium or Li-ion external batteries, 2) Inquire for different head configurations